

## **Chapter 1**

### **INTRODUCTION**

The Baby LX7 is a high-performance personal computer mainboard based on the Pentium® II processor.

The mainboard uses the highly integrated Intel®82440LX AGPset which optimize the system bandwidth and concurrency with the implementation of Quad Port Acceleration (QPA). QPA provides 4-port concurrent arbitration of the processor bus, graphics, PCI bus and SDRAM.

The Intel®82371AB chipset integrates all system control functions such as ACPI (Advanced Configuration and Power Interface). The ACPI provides more Energy Saving Features for the OSPM(OS Direct Power Management) function. The Intel®82371AB chipset also improves the IDE transfer rate by supporting Ultra DMA/33 IDE that transfers data at the rate of 33MB/s.

The mainboard also supports the Winbond 781 System Hardware Monitor Controller as optional function. The Winbond 781 function includes: CPU / power supply/chassis fan revolution detect, CPU/system voltage monitor, system temperature monitor, and chassis intrusion detect(optional).

## **1.1 Mainboard Features**

### **CPU**

- Slot 1 for Intel®Pentium®II processor.
- Supports 200MHz, 233MHz, 266MHz, 300MHz, and 333MHz.

### **Chipset**

- Intel®82440LX AGP chipset.

### **Clock Generator**

- 66.6MHz clocks are supported.

### **Main Memory**

- Supports six memory banks using three 168-pin unbuffered DIMM.
- Supports a maximum memory size of 768MB for EDO and 384MB for SDRAM.
- Supports ECC(Error Check Correct) and EC(Multiple-Bit Error Correction) function.
- Supports 3.3v Extended Data Output (EDO) and SDRAM DIMM.

### **Slots**

- One AGP(Accelerated Graphics Port) slot.
  - AGP specification compliant
  - AGP 66/133MHz 3.3v device support
- Three 32-bit Master PCI Bus slots and three 16-bit ISA bus slots
- Supports 3.3v/5v PCI bus Interface.

### **On-Board IDE**

- An IDE controller on the Intel®82371AB PCI Chipset provides IDE HDD/CD-ROM with PIO, Bus Master and Ultra DMA/33 operation modes.
- Can connect up to four IDE devices.

**On-Board Peripherals**

- On-Board Peripherals include:
  - 1 floppy port supports 2 FDD with 360K, 720K, 1.2M, 1.44M and 2.88Mbytes.
  - 2 serial ports (COMA + COMB)
  - 1 parallel port supports SPP/EPP/ECP mode
  - 2 USB ports
  - 1 IrDA connector for SIR.

**BIOS**

- The mainboard BIOS provides “Plug & Play” BIOS which detects the peripheral devices and expansion cards of the board automatically.
- The mainboard provides a Desktop Management Interface(DMI) function which records your mainboard specifications.

**On-Board System Hardware Monitor (Optional)**

- CPU/Power Supply/Chassis Fan Revolution Detect
- CPU Fan Control (the fan will automatically stop when the system enters suspend mode)
- System Voltage Detect
- Chassis Intrusion Detect(optional)
- Display Actual Current Voltage

**RTC**

- PIIX-4 (82371AB) built-in RTC.

**Dimension**

- Baby AT : 27cm(L) x 22cm(W) x 4 layers PCB


**Mounting**

- 5 mounting holes.

**Special Connector**

- LAN Wake-Up Connector.
- Internal Modem Wake-Up Connector
- Distributed DMA connector for PCI 3D Sound Card.

1.2 Mainboard Layout



MS-6118